

## Technical Specifications

<b>CPU SUPPORT</b>	Intel® Core™ 2 Duo mobile 2.2GHz FPGA with low noise fan
<b>MOTHERBOARD CORE LOGIC</b>	Intel® GME965 chipset + ICH8M
<b>MEMORY</b>	2 Dual Channel DDR2 SODIMM socket supports up to 4GB
<b>HDD SUPPORT</b>	Serial ATA SATA port with 150 MB/s transfer rate
<b>NETWORKING</b>	2x1GbE ports, Realtek RTL8111B Gigabit Ethernet
<b>AUDIO</b>	Realtek ALC286 Audio Codec, 2 + 2 watts power amplifier
<b>I/O PORTS</b>	8 USB (4 external I/O, 2 ports with on-board pin headers, and 2 ports reserved for webcam and touch screen), 1 VGA DB-15, 1 DVI output, Triple audio jack, 3 Serial Ports DB-9, 2 Keyboard/Mouse Connector, 2 LAN, 1 DC-in power connector
<b>STORAGE</b>	2.5" SATA HDD drive bay with anti-vibration mechanism, Bootable Compact Flash slot for CF type I/II storages
<b>EXPANSION SLOTS</b>	One PCI 2.2 slot One PCMCIA Type I/II 32-bit CardBus slot (optional) One 32-bit Mini-PCI socket
<b>BIOS</b>	Award BIOS, ACPI supported
<b>POWER SUPPLY</b>	Uses 100Watt AC Adapter. Input: DV12V~28V. AC 90 ~ 264V / 47 ~ 63 Hz
<b>DIMENSIONS</b>	420mm x 360mm x 85mm (W x D x H)
<b>WEIGHT</b>	Unit: 22lbs with base, 15.4lbs without base, Power Adapter: 1.9lbs.
<b>OPERATING ENVIRONMENT</b>	Operation Temperature: 0 ~ 40°C, Storage Temperature: -20 ~ 80°C, Operation Relative Humidity: 10% ~ 90% - non condensing, Storage Relative Humidity: 10% ~ 90% - non condensing
<b>ANTI-BACTERIAL COATING</b>	The plastic coating PU-206 contains 0.4% Vanquish-100 (antimicrobial) demonstrated at least 99.6% bacterial reduction after 24 hours contacting after time
<b>AVAILABLE COLORS</b>	White
<b>WATERPROOF</b>	IP65 at front side / IPX1
<b>CERTIFICATIONS</b>	CE/FCC Class B / EN60601-1 / UL60601-1, UL/cUL, VCCI
<b>DISPLAY &amp; TOUCH</b>	17" TFT LCD Panel, 400 nits, 8-wire resistive touch
<b>WALL MOUNT</b>	VESA Mount 75/100mm